



673		987		1303		1616		
SSF21	SS21	SSF31	SS31	SSF41	SS41	SSF51	SS51	511
SSF22	SS22	SSF32	SS32	SSF42	SS42	SSF52	SS52	978
SSF23	SS23	SSF33	SS33	SSF43	SS43	SSF53	SS53	1445
SSF24	SS24	SSF34	SS34	SSF44	SS44	SSF54	SS54	1911
SSF25	SS25	SSF35	SS35	SSF45	SS45	SSF55	SS55	2378
SSF26	SS26	SSF36	SS36	SSF46	SS46	SSF56	SS56	2845

## SPECIFICATION

Standard Industrial Type Steel Sashes constructed of rolled steel sections with a flanged frame bar all round, suitable for fixing to brickwork, concrete or steelwork.

Ventilators are horizontally pivoted, centrally hung on brass cup pivots and fitted with spring catch, pulley and eye for hand, cord or pole operation

Alternatively, Bottom Hung Ventilators can be supplied if specially ordered, by adding prefix "B", thus: type SSB22. Bottom Hung Ventilators are hung on steel hinges with brass pins and washers, and fitted with concealed side arms and spring catch for hand or pole operation.

Sizes are overall steel frames.

Coupling: All Standard Sashes may be coupled together by means of mullions and transoms.

Glazing is from inside.

Flyscreens can be supplied.  
Burglar bars can be supplied.

## SPESIFIKASIE

Standaard nywerheid staalrame van gewalste staalprofiel met 'n geflanse raambalk rondom geskik vir vashegting aan messelwerk, beton of staal.

Ventilators swaai horisontaal om 'n spil in die middel op geelkoperdopspille en is toegerus met veerknip, katrol en ogie vir hand-, tou- of haakstokbediening.

As alternatief kan ventilators met onderskarnier bestel word. Meld net voorkode „B", bv tipe SSB22.

Ventilators wat onder skarnier het staalskarniere met geelkoperpenne en -wasters, en is toegerus met versteekte syarms en veerknip vir hand- of haakstokbediening.

Buite mate word aangegee.

Koppeling: Alle standaardrame kan gekoppel word met tussenstyle en kalwe.

Beglazing is van binne.

Insekteskerms kan voorsien word.  
Diefwering kan voorsien word.